



TEAK & DECKING OIL

Oil for the protection of wooden surfaces



Pages: 2

113025.03.2018



Packing
0.75lt - 4lt



Bases



stir ewll before
use



Description

Mixture of oils, waxes and special additives with high penetration for protection and treatment of wooden surfaces. It is easily absorbed, revitalizes and protects wood. It is suitable for indoor and outdoor use, ideal for treating garden furniture from hardwoods such as teak, mahogany, oak, beech, rosewood as well as decks and decorative wood in boats.

Product characteristics

Product Characteristics

- High protection of wood against moisture, UV radiation, salinity.
- High penetration.
- It replaces natural oils and resins that the wood lose over time.
- Easy application.
- Great performance.
- High resistance to changes in weather conditions.
- Harmonized with Directive 2004/42/EC.

Coverage
10 - 15m²/ lt, depending on
the absorbcency and surface
type.



Drying time
Touch dry after 3
to 4 hours.



Application
brush or cloth



Application Instuctions

The product is ready for use. No thinning is required.

Surface preparation

The surface to be painted must be completely dry and clean. The product is applied by brushor cloth. In order to achieve good penetration into the wood, the product is coated in the direction of the wood lines.

New surfaces

The new surfaces are lightly rubbed with sand paper and any dust and pieces of wood are removed before the application. The product is then applied with a brush or cloth in one or two coatings. After 5 minutes of the application, wipe well with a cloth.

Old surfaces

On already painted with Teak & Decking Oil surfaces, the product is applied with a brush or cloth in one or two coatings. After applying, let it for 5 minutes and then wipe well with a cloth.

After use, clean with White Spirit the paint tools. The washes are treated as hazardous according to applicable legislation and local regulations.

Packing
0.75lt - 4lt



Technical characteristics

- **Carrier:** Mixture of oils.
- **VOC:** 400 gr/lit (maximum VOC content of ready-to-use product).
- **Viscosity:** 12 - 18 sec, 25°C (flow cup 4 DIN 53211).
- **Coverage:** 10 - 15m²/ lt, depending on the absorbency and surface type.
- **Thinning:** The product is ready for use and does not require thinning.
- **Application:** The product is applied with brush or roller.
- **Drying time:** Touch dry after 3 to 4 hours. (These times can to be extended depending on temperature and humidity).
- **Recover:** After 48 hours. (These times may be prolonged depending on temperature and humidity).

Bases



stir ewll before
use



Coverage
10 - 15m²/ lt, depending on
the absorbency and surface
type.



Drying time
Touch dry after 3
to 4 hours.



Application
brush or cloth



All the above information is based on laboratory tests and long-term experience of the company's scientific personnel. Product quality is guaranteed by our operational system, which is based on the requirements of ISO 9001, ISO 14001 and ISO 18001 Standards and EMAS Regulation. As producers we don't take any responsibility for any damage that may caused in cases that the product hasn't been used for the appropriate application and according to the application instructions.

Page 2 to 2

BERLING SA
Paint Industry

Inofita Viotias, P.C. 32011
tel.: +30 22620 31663, fax.: +30 22620 31293
www.berling.gr / info@berling.gr



Color has a Name!