



## HOBBY EFFECTS

Acrylic semitransparent coating, suitable for creating many decorative styles for interior use.



06.2021, V02

Packing: 0.5lt

### Description

Acrylic semitransparent coating, suitable for creating many decorative styles for interior use. It is applied to surfaces that have already been coated with satin or matt emulsion or acrylic paint, which has previously been tinted to the desired, using Berling's tinting system. With HOBBY Effects Berling gives the user the opportunity to use his imagination and create the style of his choice.

### Application Instructions

First apply the emulsion or acrylic paint to the shade of your choice and let it dry out well. Then pour HOBBY Effects on a paint tray. To create the desired designs, you can use a brush, sponge or other decorative style tool. When using a brush, dip it into HOBBY Effects and then apply it by working the brush in random directions on the surface. If you use a sponge, dip it into HOBBY Effects and press it lightly on the surface to get random prints. Check out Berling's DVD Decorating Styles for more ways to apply. After use, the remaining paint is removed from paint tools and then cleaned with soap and water. Washings are handled in accordance with applicable legislation and local regulations.

### Technical characteristics

<b>VOC</b>	200gr/lt (Maximum Volatile Organic Compounds content ready for use).
<b>Density</b>	1,10 ± 0,03 gr /cm <sup>3</sup> (ISO 2811).
<b>Coverage</b>	18 - 20m <sup>2</sup> /lt, depending on the type of style.
<b>Solvent</b>	Water.
<b>Thinning</b>	Ready to use product. No thinning is required.
<b>Application</b>	The product is applied with a brush, sponge, or other decorative styling tool.
<b>Drying time</b>	4-6 hours. (These times may be prolonged depending on temperature and humidity).

### ACCORDING TO 2004/42 /EC

PHASE II, Subcategory I, Decorative finishing Effects, VOC Limit Value = 200gr/lt, Maximum VOC Value= 200gr/lt (ready to use product).

## **Storage**

Keep containers tightly closed and protected from frost. After opening the container, use the product in a short time. Close the container well again. For long-term storage, it is best to keep the product indoors to avoid exposure to very low or high temperatures as well as to high humidity conditions.

## **Cautions - Environmental effects prevention**

Wear protective gloves and goggles. Do not eat or drink anything at the time of application. Wash your hands with the appropriate cleaning products. Clean tools with soap and water. Do not dispose of washing and paint remains in the sink, in the toilet or in the trash. Empty containers and paint remnants should be treated in accordance with applicable legislation and local regulations. You should ask local authorities' advice on disposal of waste.

For more information, please refer to the Product Safety Data Sheet.

*All the above information is based on laboratory tests and long-term experience of the company's scientific personnel. Product quality is guaranteed by our operational system, which is based on the requirements of ISO 9001, ISO 14001 and ISO 45001 Standards and EMAS Regulation. As producers we don't take any responsibility for any damage that may be caused in cases that the product hasn't been used for the appropriate application and according to the application instructions.*

---

## **BERLING SA**

### **Paint Industry**

Inofita Viotias, P.C. 32011

tel.: +30 22620 31663, fax.: +30 22620 31293

[www.berling.gr](http://www.berling.gr) / [info@berling.gr](mailto:info@berling.gr)

