



BAROQUE

Chalk paint for decorative effect
creations



01.04.2020 v01

Packing: 0.5 lt

Description

BAROQUE is a water-based chalk paint ideal for achieving decorative designs and styles. It is easy to use and can decorate several surfaces such as wood, metal, plastic, brick and cement surfaces and already painted or varnished surfaces after proper preparation. The main styles that can be achieved are, among other, vintage, shabby chic and decoupage.

Purpose of use

Water-based paint ideal for achieving decorative results.

Product Characteristics

- Easy to use
- Creation of many decorative designs
- Suitable for many types of surfaces
- Available in 12 ready-made and specially selected shades
- High coverage
- Matte finish with velvety texture and high chalk content
- Low content of volatile organic compounds

Shades

Available in white and 12 ready-made shades

Coverage

10 -12 m²/lt.

Application conditions

Apply at temperature from 15°C to 35°C and relative humidity up to 75%.

Application instructions

It is applied with a roller, brush, or spray gun in 1 or 2 coats depending on the desired result. To achieve two-tone effect, 2 coats of different shades can be applied each time. After the final layer, sanding is done on the desired spots and to such an extent that the substrate (which may be either the previous layer of chalk paint or our original substrate) begins to appear and the desired decorative effect is created. Do not apply to wet surfaces. Temperature and humidity conditions must be mild during application and during hardening of the material. After application and after the chalk paint is completely dry, apply the BAROQUE VARNISH protective varnish

Surface preparation

Surfaces should be dry and free of grease, oils, foreign matter and loose materials. Baroque chalk paint can be applied directly to a number of surfaces such as wooden, concrete, already painted and varnished surfaces. In all types of these surfaces, but also in others such as metal, galvanized, glass, PVC plastic can be used BERLING ALL PURPOSE PRIMER to achieve even better adhesion and especially in non-absorbent and difficult substrates. On already painted surfaces with plastic or acrylic paints and if they have not been chalked, chalk paint can be applied directly. If there is chalking, then the AQUAFIX primer must first be applied. On surfaces already varnished or painted with alkyd paints it is advisable to pre-sand with sandpaper before applying the chalk paint.

Technical characteristics

Specific gravity	1,65 ± 0,02 (ISO 2811).
Viscosity	120 – 125 K.U., 25°C (ASTM D562).
pH	8,5 ± 0,3.
Coverage	10 – 12 m ² /lt depending on the type of the surface and the application method.
Drying	Touch dry ½ -1 hour, depending on weather conditions. Through dry after at least 24 hours (These times may be elongated depending on temperature and humidity conditions).
Recoat	After 6 hours depending on weather conditions. (These times may be elongated depending on temperature and humidity conditions). Chalk paint can be easily sanded after proper drying
Final cure	The product acquires its final properties in 7 days from the final coating and in mild conditions of temperature and humidity. 24 hours after applying the final coat of paint can be varnished with the protective varnish Baroque varnish
Solvent	Water.
Thinning	The percentage of thinning is determined by the desired decorative effect and by the method of application. It is recommended to thin with water at a rate of 5 - 10% by volume for application with a roller or brush. For spray gun application, the recommended thinning is 15-20% by volume

According to 2004/42/EC

Phase II, Subcategory i) decorative effect coatings, V.O.C content limit value = 200gr/l, Maximum V.O.C. Content = 20gr/l (thinned, ready to use). Thinning: up to 20 % by volume with water.

Storage

Keep cans air - tight sealed and protect from frost. For long - term storage the product is best kept indoors in order to avoid its exposure to very low or very high temperatures as well as high humidity conditions. Store away from food, drinks and animal food stuff. Keep out of reach of children. After opening the can, use the product in a short time.

Instructions precautions - Prevent environmental impact

Keep out of the reach of children. Wear protective goggles and gloves. Do not drink, eat or smoke while using the product. Wash hands thoroughly after work. Do not discard paint remnants in the drainage or aquifer. Empty containers and paint remnants must be disposed of in accordance with applicable laws and local regulations.

For more information, please refer to the Material Safety Data Sheet.

All the above information is based on laboratory tests and long-term experience of the company's scientific personnel. Product quality is guaranteed by our operational system, which is based on the requirements of ISO 9001, ISO 14001 and OHSAS 18001 Standards and EMAS Regulation. As producers we don't take any responsibility for any damage that may caused in cases that the product hasn't been used for the appropriate application and according to the application instructions.

BERLING SA

Paint Industry

Inofita Viotias, P.C. 32011

tel.: +30 22620 31663, fax.: +30 22620 31293

www.berling.gr / info@berling.gr

