

# PETITE MATT BASIC COLOURS

High quality, matt, colored emulsion paints



06.2024 V.03

High quality, matt, colored emulsion paints, suitable for indoor use. They are applied on all well-prepared surfaces, giving a beautiful aesthetically result, homogenous, smooth with matt finish.



**Stir well before use**



**Coverage:**  
15-17m<sup>2</sup>/lt,



**Drying time:**  
Touch dry from 1 to 2 hours



**Thinning**  
with water at a percentage of 10-15% v/v



**Paint:**  
Roller



**Paint:**  
Brush

## Product Characteristics

- Very good adhesion.
- High scrub resistance.
- Excellent performance
- Matt finish.

## Shades

Available in 8 ready shades

## Packaging:

**0.200lt**  
**0.375lt**  
**0.75lt**

**Available in 3lt: yellow, red, black, blue, ochre**

**Available in 9lt: black**



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

## Technical Specifications



<b>V.O.C</b>	30gr/lit (Maximum Volatile Organic Compounds content ready for use).
<b>Viscosity</b>	95-110 K.U., 25°C (ASTM D562) (for white).
<b>pH</b>	7,7-8,7
<b>Wet Abrasion Resistance</b>	Class 1 (EN ISO 11998, EN 13300)
<b>Performance</b>	15-17m <sup>2</sup> /lit, per coating
<b>Thinning</b>	Thin with water at 10 - 15% by volume, depending on the application method.
<b>Application</b>	The product is applied by brush or roller.
<b>Drying time</b>	Touch dry 1- 2 hours, depending on the weather conditions. (drying time might be elongated according to temperature and humidity conditions)
<b>Recoating</b>	Repaint after 6 hours, depending on weather conditions. (drying time might be elongated according to temperature and humidity conditions).

### ACCORDING TO 2004/42/EK

PHASEII,  
Subcategory a,  
Matt coatings for  
interior walls and  
ceilings, Value limit  
V.O.C.= 30gr/lit,  
max VOC.=30gr/lit  
(ready to use  
product).



### Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



### Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.  
**For further information ask for the Safety Data Sheet of the product.**

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

## Recommended application systems

### Interior walls

- **New surfaces**

#### Preparation

For perfect results on new surfaces, it is recommended to use Berling's Stuco Grid putty, following the application instructions.

#### STUCO GRID

2 COATS

#### Primer

Prime with Nature Aquafix, Berling Nanoprimer or Acrylic Emulsion Primer, following the application instructions.

#### NATURE AQUAFIX or BERLING NANOPRIMER or ACRYLIC EMULSION PRIMER

1 COAT

#### Final coating

For a uniform and impressive result apply 2 coatings with Petite Matt Basic.

#### PETITE MATT BASIC

2 COATS

- **Old- already painted surfaces**

#### Preparation

On already painted but healthy, non-stained surfaces, no special preparation is required. In the case of puttied surfaces, rubbing with sandpaper is required.

#### Primer

For puttied and chalked surfaces or covered with distemper or lime it is necessary to prime them first with Berling Nanoprimer.

#### BERLING NANOPRIMER

1 COAT

#### Final coating

For a uniform and impressive result apply 2 coatings with Petite Matt Basic.

#### PETITE MATT BASIC

2 COATS

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

## Recommended application systems

### Plasterboard surfaces

- **New surfaces**

#### Preparation

For perfect results on new surfaces, it is recommended to use Berling's Stuco Grid putty, following the application instructions.

#### STUCO GRID

2 COATS

#### Primer

In case of putting the whole surface, prime with Berling Nanoprimer. If no puttying procedure is required then use Berling Plasterboard Primer, following its application instructions.

#### BERLING NANOPRIMER or PLASTERBOARD PRIMER

1 COAT

#### Final coating

For a uniform and impressive result apply 2 coatings with Petite Matt Basic.

#### PETITE MATT BASIC

2 COATS

- **Old- already painted surfaces**

#### Preparation

On already painted but healthy, non-stained surfaces, no special preparation is required. In the case of puttied surfaces, rubbing with sandpaper is required.

#### Primer

For puttied and chalked surfaces or covered with distemper or lime it is necessary to prime them first with Berling Nanoprimer.

#### BERLING NANOPRIMER

1 COAT

#### Final coating

For a uniform and impressive result apply 2 coatings with Petite Matt Basic.

#### PETITE MATT BASIC

2 COATS

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.