

# WHITE ACRYLIC PRIMER

White semi-transparent primer



11.2023 V.02

White, semi-transparent, 100% acrylic primer for internal and external use for both emulsion and acrylic paints. Suitable for all types of surfaces such as plaster, bricks, plasterboard, and surfaces already painted with emulsion or acrylic paints. It has good adhesion, high performance and facilitates the application of the final coating. It excels over the other primers due to its translucency, which improves the coverage of the final coating while at the same time it can be tinted in the shade of the final paint.



**Stir well before use**



**Coverage:**  
12-14 m<sup>2</sup>/lt



**Drying time:**  
Touch dry 2 to 4 hours



**Thinning**  
with water at a percentage of 30-50% v/v



**Paint:**  
Roller



**Paint:**  
Brush

## Product Characteristics

- White semi-transparent substrate.
- It is tinted in light-color shades, by improving the coverage.
- High adhesion.
- High performance.
- Low Volatile Organic Compound content.

## Shades

Available in white and it can be tinted in many shades base on Berling's tinting system.

## Packaging:

0.75lt  
4lt  
10lt



**EPD**<sup>®</sup>

THE INTERNATIONAL EPD<sup>®</sup> SYSTEM

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry  
Inofita Viotias, P.C. 32011, Greece  
tel.: +30 22620 31663, fax.: +30 22620 31293  
www.berling.gr /en info@berling.gr

## Technical Specifications



<b>V.O.C</b>	10gr/lit (maximum Volatile Organic Compound content ready to use product).
<b>Density</b>	1,20 ± 0,03gr/cm <sup>3</sup> (ISO 2811).
<b>Viscosity</b>	60 - 80 K.U., 25°C (ASTM D562).
<b>pH</b>	7,7-8,7
<b>Coverage</b>	12-14m <sup>2</sup> /lit, depending on application method
<b>Thinning</b>	Thinned with water at a percentage of 30 - 50% by volume, depending on application method.
<b>Application</b>	The product is applied by brush or roller
<b>Drying time</b>	Touch dry 2 -4 hours. (These times may be extended depending on temperature and humidity).
<b>Recoating</b>	After 6 hours. (These times may be extended depending on temperature and humidity).

### ACCORDING TO 2004/42/EK

PHASEII,  
Subcategory g,  
Primers, Limit VOC  
value= 30gr/lit,  
Maximum VOC  
value= 10gr/lit  
(product ready for  
use).



### Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



### Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.  
**For further information ask for the Safety Data Sheet of the product.**

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

## Recommended application systems

### Interior/Exterior surfaces

- **New/Old surfaces**

#### Preparation

Surfaces to be painted should be dry and clean of any dust, grease, salt, and old peeled paints. If necessary, putty with Berling's Acrylic Putty or Stuco Grid, before product application, always following their application instructions.

#### **STUCO GRID or ACRYLIC PUTTY**

2 coats

#### Primer

Prime with white acrylic primer, following its application instructions.

#### **WHITE ACRYLIC PRIMER**

1 coat

#### Final coating

For a uniform and impressive result apply 2 coats of Berling's Emulsion or Acrylic paint.

#### **BERLING'S EMULSION or ACRYLIC PAINT**

2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.