

PETITE CLASSIC MATT

Top Odorless Matt Emulsion Paint

for Indoor Use

07.2022 V.01

Excellent quality odorless, with very low volatile compounds emulsion matt paint for internal use, suitable for all kinds of surfaces. Its advanced synthesis gives an excellent aesthetic result with main characteristics high coverage and whiteness, uniform spread and levelling and good resistance to washing. The combination of the above with the absence of odors during, and after painting, makes it an excellent choice for interior use.



Stir well before use



Coverage:
14-16m²/lt



Drying time:
Between 1 to 1,5 hrs



Thinning
with water at a percentage of 10 - 15% v/v



Paint:
Roller



Paint:
Brush

Product Characteristics

- Odorless interior wall paint
- Excellent coverage.
- Very low content of Volatile Organic Compounds.
- High whiteness.
- High performance.
- Very good adhesion.
- Full matt finish
- High resistance to wet cleaning.
- High resistance to rubbing.
- Easy to apply.

Shades

Available in white and three bases (Base A, Base B and Base C) to create thousands of shades with Berling's tinting system

Packaging:

White
0.375lt
0.75lt
3lt
10lt
Bases
0.75lt
3lt
9lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



V.O.C	<8,5 gr/lit (Maximum Volatile Organic Compounds content ready for use).
Density	1,66± 0,03gr/cm ³ (ISO 2811) (for white).
Viscosity	115-125 K.U., 25°C (ASTM D562) (for white).
pH	8,0-9,0
Wet Abrasion Resistance	Class 2 (EN ISO 11998, EN 13300)
Performance	14 - 16m ² /lit, per coat.
Gloss	2 - 2,5 units at an angle 60°.
Thinning	Thin with water at a percentage of 10-15% by volume, depending on the application method.
Application	The product is applied by brush or roller
Drying	Touch dry 1- 1,5 hrs, depending on the weather conditions. (The drying time might be elongated according to temperature and humidity conditions)
Recoating	Repaint after 2-4 hrs, depending on weather conditions. (The drying time might be elongated according to temperature and humidity conditions)

ACCORDING TO 2004/42/EK

PHASE II,
Subcategory a,
Matt coatings for
interior walls and
ceilings, Value limit
V.O.C.= 30gr/lit,
max VOC.=<8,5
gr/lit (ready to use
product)



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

Recommended application systems



Interior walls

New surfaces

Preparation

For smoother results on new surfaces, it is recommended to use Berling's Stuco Grid putty, following the application instructions.

STUCO GRID
2 coats

Primer

Prime with Nature Aquafix or Acrylic Emulsion Primer, following the application instructions. When choosing dark shades, prime with Acrylic White Primer tinted in close or similar shade according to Berling's tinting system, to reduce the number of final coats.

**AQUAFIX NATURE
ACRYLIC EMULSION PRIMER**

ACRYLIC WHITE PRIMER

1 coat

Final coating

For a uniform and impressive result apply 2 coatings with Petite Classic Matt

PETITE CLASSIC MATT
2 coats

• Old- already painted surfaces

Preparation

On already painted but healthy, non-stained surfaces, no special preparation is required. In the case of puttied surfaces, sanding with sandpaper is required.

Primer

For surfaces that are puttied and sanded and surfaces that have been chalked or covered with distemper paint or lime, it is required to be primed with Berling's primer Nature Aquafix.

**AQUAFIX NATURE
AQUASIL**

1 coat

If the surface is stained by exhaust gases, smoke or other household pollutants, it is required to be primed with Berling's Nature Aquasil primer, before applying the product.

Final coating

For a uniform and impressive result apply 2 coatings with Petite Classic Matt

PETITE CLASSIC MATT
2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Recommended application systems



Plasterboard surfaces

• New surfaces

Preparation

If necessary, putty with Berling Stuco Grid, following its application instructions.

STUCO GRID
2 coats

Primer

In case of putting the whole surface, prime with Nature Aquafix, Acrylic emulsion primer or Berling Nanoprimer.

If no puttying procedure is required, then use Berling Plasterboard primer, following its application instructions. Plasterboard Primer can be tinted in close or similar shade according to Berling's tinting system, to reduce the number of final coats.

**AQUAFIX NATURE
ACRYLIC EMULSION PRIMER
BERLING NANOPRIMER
PLASTERBOARD PRIMER**
1 coat

Final coating

For a uniform and impressive result apply 2 coatings with Petite Classic Matt

PETITE CLASSIC MATT
2 coats

• Old-already painted surfaces

Preparation

On already painted but healthy, non-stained surfaces, no special preparation is required. In the case of puttied surfaces, sanding with sandpaper is required.

Primer

For surfaces that are puttied and sanded and surfaces that have been chalked or covered with distemper paint or lime, it is required to be primed with Berling's primer Nature Aquafix.

If the surface is stained by exhaust gases, smoke or other household pollutants, it is required to be primed with Berling's Nature Aquasil primer, before applying the product.

**AQUAFIX NATURE
AQUASIL**
1 coat

Final coating

For a uniform and impressive result apply 2 coatings with Petite Classic Matt

PETITE CLASSIC MATT
2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.