

# 100% ACRYLIC PAINT PROFESSIONAL

Acrylic- colored paint



12.2022 V.02

High quality, acrylic colored paint, suitable for exterior use on well prepared surfaces and especially for visible concrete and asbestos cement surfaces. It has high adhesion, opacity, and resistance to weather changes.



**Stir well before use**



**Coverage:**  
10-13 m<sup>2</sup>/lt



**Drying time:**  
Between 2 to 4 hrs



**Thinning**  
with water at a percentage of 10-15% by volume



**Paint:**  
Roller



**Paint:**  
Brush

## Product Characteristics

- Tile red/grey - colored coating.
- Matt finish.
- High coverage.
- Very good adhesion and opacity.
- Great resistance against weather condition changes.
- Easy to apply.
- Free of ammonia, lead, mercury and other heavy metals.
- Low content in Volatile Organic Compounds.
- Harmonized with directive 2004/42/EC.

## Shades

Available in grey and red tile.

**Packaging:**  
0,6lt  
3lt  
9lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

## Technical Specifications



<b>V.O.C</b>	25gr/ltr ( Maximum Volatile Organic Compounds content ready for use).
<b>Density</b>	1,50 ± 0,05 gr /cm <sup>3</sup> (ISO 2811).
<b>Viscosity</b>	105-120 K.U., 25°C (ASTM D562).
<b>pH</b>	8,0 ± 0,2
<b>Performance</b>	10-13m <sup>2</sup> /ltr, per coat.
<b>Gloss</b>	0,5 - 1,0 units in 60° angle.
<b>Thinning</b>	Thin with water at a percentage of 10-15% by volume, depending on the application method.
<b>Application</b>	The product is applied by brush or roller
<b>Drying</b>	Touch dry 2-4hrs, depending on the weather conditions. (The drying time might be elongated according to temperature and humidity conditions)
<b>Recoating</b>	Repaint after 4 to 6 hrs, depending on weather conditions. (The drying time might be elongated according to temperature and humidity conditions)

### ACCORDING TO 2004/42/EK

PHASEII,  
Subcategory c, for exterior walls of mineral substrate, value limit VOC = 40gr/ltr, max VOC value limit= 25gr/ltr (ready to use product).



### Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



### Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.  
**For further information ask for the Safety Data Sheet of the product.**

## Recommended application systems



### Interior and Exterior Walls

#### • New surfaces

##### Preparation

Surfaces must be dry and clean from dust, grease, alkali and older peeled/ chocked paints. If there are any holes, cracks or wall irregularities use the Acrylic Putty, before applying Acrylic Paint Professional.

##### ACRYLIC PUTTY

1 coat

##### Primer

In case of already painted but healthy and stable surfaces, no priming is needed. In case of loose substrates, after preparing them, prime with a primer suitable for exterior use, such as Fixateur. In case of surfaces with alkali salts use Berling's Super Primer before the final coats.

##### FIXATEUR SUPER PRIMER

1 coat

##### Final coating

For a uniform and impressive result apply 2 coatings with Acrylic Paint Professional.

##### ACRYLIC PAINT PROFESSIONAL

2 coats

#### • Old- already painted surfaces

##### Preparation

In case of already painted or treated with putty surfaces, or in case of old peeled or chalked paints, sand first with a sand paper.

##### Primer

In case of already painted but healthy and stable surfaces, no priming is needed. In case of loose substrates, after preparing them, prime with a primer suitable for exterior use, such as Fixateur. In case of surfaces with alkali salts use Berling's Super Primer before the final coats.

##### FIXATEUR SUPER PRIMER

1 coat

##### Final coating

For a uniform and impressive result apply 2 coatings with Acrylic Paint Professional.

##### ACRYLIC PAINT PROFESSIONAL

2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.