

# HAUS OUT

Water-based acrylic paint



04.2023 V.03

Economic, acrylic paint suitable for exterior use and especially for surfaces that require often repainting.



**Stir well before use**



**Coverage:**  
8-11 m<sup>2</sup>/lt



**Drying time:**  
Between 2 to 4 hrs.



**Thinning**  
with water at a percentage of 16% by volume



**Paint:**  
Roller



**Paint:**  
Brush

## Product Characteristics

- Matt finish
- Good coverage
- Good adhesion
- Good opacity
- Good whiteness
- Easy to apply
- Very low Volatile Organic Compounds content

## Shades

Available in white.

## Packaging:

White  
3lt  
9lt  
16lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry  
Inofita Viotias, P.C. 32011, Greece  
tel.: +30 22620 31663, fax.: +30 22620 31293  
www.berling.gr /en info@berling.gr

## Technical Specifications



<b>V.O.C</b>	10gr/lt ( Maximum Volatile Organic Compounds content ready for use).
<b>Density</b>	1,42 ± 0,03gr /cm <sup>3</sup> (ISO 2811) (for white).
<b>Viscosity</b>	100-110 K.U., 25°C (ASTM D562) (for white).
<b>pH</b>	7,7-8,7
<b>Performance</b>	08-11m <sup>2</sup> /lt, per coat.
<b>Thinning</b>	Thin with water at a percentage of 16% by volume, depending on the application method.
<b>Application</b>	The product is applied by brush or roller
<b>Drying</b>	Touch dry 2-4hrs, depending on the weather conditions. (The drying time might be elongated according to temperature and humidity conditions)
<b>Recoating</b>	Repaint after 4-6 hrs, depending on weather conditions. (The drying time might be elongated according to temperature and humidity conditions)

### ACCORDING TO 2004/42/EK

PHASE II,  
Subcategory c,  
Exterior walls and  
mineral substrate,  
Value limit V.O.C.=  
40gr/lt, max  
VOC.=10gr/lt  
(ready to use  
product).



### Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



### Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.  
**For further information ask for the Safety Data Sheet of the product.**

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry  
Inofita Viotias, P.C. 32011, Greece  
tel.: +30 22620 31663, fax.: +30 22620 31293  
www.berling.gr /en info@berling.gr

## Recommended application systems



### Interior walls and Plasterboard surfaces

- **New surfaces**

#### Preparation

For smoother results on new surfaces, it is recommended to use Berling's Stuco Grid putty, following the application instructions.

**STUCO GRID**  
2 coats

#### Primer

Prime with primer suitable for exterior use (such as Fixateur, Super Primer, Nature Aquafix), following their application instructions.

**FIXATEUR or SUPER PRIMER  
or NATURE AQUAFIX**  
1 coat

#### Final coating

For a uniform and impressive result apply 2 coatings with Haus Out.

**HAUS OUT**  
2 coats

- **Old- already painted surfaces**

#### Preparation

On already painted but healthy, non-stained surfaces, no special preparation is required. In the case of puttied surfaces, sanding with sandpaper is required.

#### Primer

In case of loose substrates, after preparing them as mentioned above, prime with a primer suitable for exterior use (such as Fixateur, Super Primer, Acrylic Emulsion Primer, Nature Aquafix). For chalked surfaces use primer Fixateur or Nature Aquafix to stabilize them, before applying Haus Out. In case of surfaces with alkali salts use Berling's Super Primer before the final coats.

**FIXATEUR or SUPER PRIMER  
or ACRYLIC EMULSION  
PRIMER or NATURE  
AQUAFIX**  
1 coat

#### Final coating

For a uniform and impressive result apply 2 coatings with Haus Out.

**HAUS OUT**  
2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.