

RELIEF

Acrylic textured coating

05.2025 V.04

Relief is a high quality acrylic textured coating, suitable for all type of well-prepared surfaces. It has good waterproofing properties giving a relief decorative effect. It has very good adhesion, high performance and is very resistant to changes in weather conditions. Due to its embossed shape, which depends on the roller to be used, it is able to cover any cracks or defects on the wall.



Stir well before use



Coverage:
3-5 m²/lt



Drying time:
Touch dry after 4 to 6 hours



Thinning
Ready to use product.



Paint:
Roller



Paint:
Spatula

Product Characteristics

- Embossed decorative effect.
- Acrylic and waterproofing coating
- Very good adhesion
- High resistance to changes in weather conditions.
- Very Low Volatile Organic Compounds Content.
- Harmonized with Directive 2004/42 / EC.

Packaging:

3lt
9lt



Shades

Available in white

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



V.O.C.	10gr/lit (max content in Volatile Organic Compounds of thinned - ready to use product)
Specific gravity	1,68 ± 0,02gr/cm ³ (ISO 2811)
Viscosity	Highly thixotropic.
pH	7,8 ± 0,3
Performance	3 - 5m ² /lit, depending on the film thickness and the application method.
Thinning	It is thinned with water up to 17% by volume, depending on the final form of the coating you want. For denser textured effect the product is not thinned.
Application	The product is applied with a special roller or spatula.
Drying time	Touch dry after 4 to 6 hours, depending on weather conditions and film thickness. (These times can be extended depending on the temperature and humidity).
Recoating	After 6 to 8 hours, depending on weather conditions and film thickness. (These times can be extended depending on the temperature and humidity).

ACCORDING TO 2004/42/EK

PHASE II,
 Subcategory c,
 Exterior wall of mineral substrate, value limit VOC = 40gr/lit, max VOC value limit = 10gr/lit (ready to use product).



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use. **For further information ask for the Safety Data Sheet of the product.**

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Recommended application systems

Interior/ Exterior surfaces

SURFACE PREPARATION

The surfaces to be painted should be dry and free from dust, grease, salts and old peeled paints. Any holes, cracks, or unevenness of the wall should be previously stocked with Berling's Acrylic Putty. Apply the product with a special roller or spatula after proper thinning. Application is carried out at ambient temperature from 10°C to 35°C and maximum relative humidity 80%.

APPLICATION INSTRUCTIONS

On new surfaces Relief is thinned 50% by weight with water and used instead of a primer on the surface to be painted. The surface is then repainted, following the instructions of Relief without thinning to achieve the desired textured decorative effect. In the case of already painted or stained surfaces or on chalked surfaces, old paints or lime coated, Berling's Fixateur primer is required and then Relief is applied in the same way as in new surfaces.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.