

BLACK BOARD PAINT

Water based paint for creating blackboard surfaces.

05.2025 V.03

Waterbased paint with special composition, based on acrylic resins. Suitable for creating blackboard surfaces. It results in an excellent aesthetic decorative effect with high resistance. It is applied on indoor surfaces, new or already painted, such as walls, wood, MDF, plywood, metal ect, after suitable preparation.



Stir well before use



Coverage:
10-12 m²/lt



Drying time:
Between 1 to 2 hrs.



Thinning
With water at percentage 8 to 10% by volume.



Paint:
Roller



Paint:
Brush

Product Characteristics

- Excellent aesthetic result.
- High resistance to frequent use.
- High resistance to frequent wet cleaning.
- Does not display shades of chalk. (Anti Ghosting Effect)

Packaging:

0,375lt
0,75lt



Shades

Available in black.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.



V.O.C	70gr/lit (Maximum Volatile Organic Compounds content ready for use).
Viscosity	85 – 95 K.U. (ASTM D562).
Performance	10 - 12 m ² /lit depending on application method.
Thinning	Thinned with water at a percentage 8-10% by volume.
Application	The product is applied by brush or roller
Drying	Touch dry from 1 to 2 hrs, depending on the weather conditions. (The drying time might be elongated according to temperature and humidity conditions)
Recoating	Repaint after 6 hrs, depending on weather conditions. (The drying time might be elongated according to temperature and humidity conditions)

ACCORDING TO 2004/42/EK

Phase II,
Subcategory I-
decorative effect
coatings, V.O.C
content limit value
= 200gr/lit.,
Maximum V.O.C.
Content = 70gr/lit
(thinned, ready to
use), Thinning: up to
10% by volume with
water.



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Recommended application systems

Interior surfaces

- New surfaces / Already painted surfaces

Application Instructions

Apply by brush or roller after suitable thinning. The final strength of the product is achieved at least after 3 days. Use of the surface 3 days after product application. Cleaning with wet means 10 days after product application.

Preparation

Surfaces must be clean, dry, free from loose materials, greases, mould etc. In case of surfaces already painted with water or solvent based enamel paints, sanding, and cleaning by mechanical means (sandpaper, refiner etc) is required.

Primer

In case of chalking or loose substrates painted with water-based emulsion or acrylic paints first stabilize with Nature Aquafix.

NATURE AQUAFIX

1 COAT

In case of enamel paints no primer is required after the described above preparation.

Final coating

For a uniform and functional result apply 3 coatings with BLACK BOARD PAINT.

BLACK BOARD PAINT

3 COATS

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.