

# BAROQUE

Chalk paint for decorative effect creations

03.2026 V.04

BAROQUE is a water-based chalk paint ideal for achieving decorative designs and styles. It is easy to use and can decorate several surfaces such as wood, metal, plastic, brick and cement surfaces and already painted or varnished surfaces after proper preparation. The main styles that can be achieved are, among other, vintage, shabby chic and decoupage.



**Stir well before use**



**Coverage:**  
10-12 m<sup>2</sup>/lt



**Drying time:**  
Touch dry ½ -1 hour



**Thinning**  
With water at percentage 15 to 20% by volume.



**Paint:**  
Roller



**Paint:**  
Brush

## Product Characteristics

- Easy to use
- Creation of many decorative designs
- Suitable for many types of surfaces
- Available in 12 ready-made and specially selected shades
- High coverage
- Matte finish with velvety texture and high chalk content
- Low content of volatile organic compounds

## Shades

Available in white and 12 ready-made shades.

## Packaging:

0,5lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.



<b>V.O.C</b>	20gr/lit ( Maximum Volatile Organic Compounds content ready for use).
<b>Viscosity</b>	120 – 125 K.U., 25°C (ASTM D562).
<b>Performance</b>	10 – 12 m <sup>2</sup> /lit depending on the type of the surface and the application method.
<b>Thinning</b>	The percentage of thinning is determined by the desired decorative effect and by the method of application It is recommended to thin with water at a rate of 5 - 10% by volume for application with a roller or brush. For spray gun application, the recommended thinning is 15-20% by volume.
<b>Application</b>	The product is applied by brush or roller
<b>Drying</b>	Touch dry ½ -1 hour, depending on weather conditions. Through dry after at least 24 hours (These times may be elongated depending on temperature and humidity conditions).
<b>Final cure</b>	The product acquires its final properties in 7 days from the final coating and in mild conditions of temperature and humidity. 24 hours after applying the final coat of paint can be varnished with the protective varnish Baroque varnish
<b>Recoating</b>	Repaint after 6 hrs, depending on weather conditions. (The drying time might be elongated according to temperature and humidity conditions)

**ACCORDING TO 2004/42/EK**

Phase II, Subcategory i) decorative effect coatings, V.O.C content limit value = 200gr/lit, Maximum V.O.C. Content = 20gr/lit (thinned, ready to use), Thinning: up to 20 % by volume with water



**Storage**

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



**Safety Instructions- Prevention of environmental harming**

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use. **For further information ask for the Safety Data Sheet of the product.**

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

## Recommended application systems

### Interior surfaces

- New surfaces / Already painted surfaces

#### Application Instructions

It is applied with a roller, brush, or spray gun in 1 or 2 coats depending on the desired result. To achieve two-tone effect, 2 coats of different shades can be applied each time.

After the final layer, sanding is done on the desired spots and to such an extent that the substrate (which may be either the previous layer of chalk paint or our original substrate) begins to appear and the desired decorative effect is created.

Do not apply to wet surfaces. Temperature and humidity conditions must be mild during application and during hardening of the material. After application and after the chalk paint is completely dry, apply the BAROQUE VARNISH protective varnish

#### Preparation

Surfaces should be dry and free of grease, oils, foreign matter and loose materials. Baroque chalk paint can be applied directly to a number of surfaces such as wooden, concrete, already painted and varnished surfaces. In all types of these surfaces, but also in others such as metal, galvanized, glass, PVC plastic can be used BERLING ALL PURPOSE PRIMER or EXPERT PRIMER to achieve even better adhesion and especially in non-absorbent and difficult substrates.

On already painted surfaces with plastic or acrylic paints and if they have not been chalked, chalk paint can be applied directly. If there is chalking, then the AQUAFIX primer must first be applied.

On surfaces already varnished or painted with alkyd paints it is advisable to pre-sand with sandpaper before applying the chalk paint.