

PLASTERBOARD PRIMER

White water-based primer



08.2023 V.03

White, water-based, acrylic primer, for interior surfaces with excellent filling capacity and high coverage. It is designed to reduce the absorbency of the surface to be painted and especially for plasterboard and other structural surfaces such as plaster, concrete, etc., contributing to the coverage and uniformity of the final paint.



Stir well before use



Performance:
18 - 20m² /lt



Drying time:
Touch dry in 30-60 minutes.



Thinning:
With water up to 20% by volume.



Application:
By roller



Application:
By brush



Application:
By airless gun

Product Characteristics

- Excellent filling capacity.
- Reduces the absorbency of plasterboard.
- Very good adhesion.
- Great coverage.
- It can be tinted in light shades.
- Excellent result with just one coating.
- Low Volatile Organic Compounds content.

Shades

Available in white and tinted in many shades according to Berling's tinting system.

Packaging:

3lt
10lt



EPD[®]
THE INTERNATIONAL EPD[®] SYSTEM

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry
Inofita Viotias, P.C. 32011, Greece
tel.: +30 22620 31663, fax.: +30 22620 31293
www.berling.gr /en info@berling.gr

Technical Specifications



V.O.C	15 gr/lit (Maximum Volatile Organic Compounds content ready for use).
Density	1,39 ± 0,03gr/cm ³ (ISO 2811).
Viscosity	90-110 K.U., 25°C (ASTM D562).
pH	7.7-8.7
Performance	18 - 20m ² /lit, similar absorbency of the surface to be painted.
Thinning	With water up to 20% by volume for roller or brush application and up to 30% by volume for air gun application.
Application	The product is applied by brush, roller or by airless spray.
Drying	Touch dry in 30-60 minutes. (These times may be extended depending on temperature and humidity)
Recoating	Recoat after 8 hours. (These times may be elongated depending on temperature and humidity).

ACCORDING TO 2004/42/EK

PHASE II,
Subcategory g,
Primers, VOC limit
value = 30gr /lit,
Maximum VOC
value= 15gr/lit
(Ready to use
product).



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry
Inofita Viotias, P.C. 32011, Greece
tel.: +30 22620 31663, fax.: +30 22620 31293
www.berling.gr /en info@berling.gr

Recommended application systems



Interior surfaces – New

- New interior surfaces

Preparation

Before the application if it is needed, putty the surface with Berling's Acrylic Putty or Berling's Stuco Grid, in accordance with their application instructions. If it is to be applied to the entire surface of the plasterboard Stuco Grid, then it is better to use a penetrating primer.

BERLING ACRYLIC PUTTY or BERLING STUCO GRID

1 coat

Primer

Prime with Plasterboard primer following its application instructions.

PLASTERBOARD PRIMER

1 coat

Final coating

For a uniform and impressive result apply 2 coats with Berling's Emulsion paint for interior use.

BERLING EMULSION PAINT

2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.