

# PAINT REMOVER

Special product for removal of old paints and varnishes



05.2025 V.03

New composition and technology Berling's Paint Remover. It is used for the removal of old paints and varnishes from various surfaces. It is also suitable for the removal of polyurethane and epoxy systems.



## Application Instructions

It is applied by brush in a thick coating. It is left to act from 10 to 20 minutes after which old paints are softened or swelling. If the action of the product is not visible, check with stripping knife or spatula if the old paint is already softened. In case of undesirable results repeat use and leave the product to act for longer time. The process is also repeated in case the coating of old paint is very thick.

After use remove the remaining product and clean tools with water. Handle eluants as dangerous waste according to local regulations and valid legislation.

## Packaging:

0.5Kg

1Kg



## Technical specifications

|                  |                                                           |
|------------------|-----------------------------------------------------------|
| Composition      | Mixture of special solvents.                              |
| Specific Gravity | 0,95 ± 0,02gr/ml                                          |
| Thinning         | The product is ready to use. No thinning is required.     |
| Drying time      | The product evaporates and stops to act after 30 minutes. |

Οι παραπάνω πληροφορίες είναι βασισμένες σε ελέγχους εργαστηρίων και στην μακρόχρονη εμπειρία του επιστημονικού προσωπικού της εταιρείας. Η ποιότητα του προϊόντος είναι εγγυημένη από το λειτουργικό σύστημα της εταιρείας το οποίο είναι βασισμένο στις απαιτήσεις των προτύπων ISO 9001, ISO 45001, ISO 14001 και τον κανονισμό EMAS. Ως παραγωγοί δε φέρουμε καμία ευθύνη για οποιεσδήποτε ζημιές ή φθορές προκληθούν στην περίπτωση που το προϊόν δεν έχει χρησιμοποιηθεί για την κατάλληλη εφαρμογή και σύμφωνα με τις οδηγίες χρήσης του.