

PETITE SATIN

Excellent quality, ecological emulsion paint

03.2026 V.05

Excellent quality, ecological, emulsion paint, suitable for all kinds of interior surfaces and especially for children's bedrooms. It has high resistance to washing, and a smooth, satin finish. The first Greek paint awarded with the European Ecolabel.



Stir well before use



Coverage:
9-11 m²/lt



Drying time:
Between 2 to 4 hrs



Thinning
with water at a percentage of 10-15% by volume



Paint:
Roller



Paint:
Brush



Paint:
Airless gun

Product Characteristics

- Satin finish
- Excellent adhesion
- Excellent opacity
- Excellent coverage
- High washing resistance
- High whiteness
- Satin finish
- Easy to apply
- Very low Volatile Organic Compounds content.
- Awarded with the EU Ecolabel. (Registry No EL / 044/001).

Shades

Available in white and two bases (Base A, Base C) to create thousands of shades with Berling's tinting system

Packaging:

White

0.75lt

3lt

10lt

Bases

0.75lt

3lt



EPD[®]

THE INTERNATIONAL EPD[®] SYSTEM

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



V.O.C	10 gr/lit (Maximum Volatile Organic Compounds content ready for use).
Density	1,38± 0,03gr/cm ³ (ISO 2811) (for white).
Viscosity	115-125 K.U., 25°C (ASTM D562) (for white).
pH	7,7-8,7
Wet Abrasion Resistance	Class 1 (EN ISO 11998/EN 13300)
Performance	9-11 m ² /lit, per coat.
Gloss	13-18 units at an angle 60°.
Thinning	Thin with water at a percentage of 10-15% by volume, depending on the application method.
Application	The product is applied by brush or roller or airless gun.
Drying	Touch dry 2-4hrs, depending on the weather conditions. (The drying time might be elongated according to temperature and humidity conditions)
Recoating	Repaint after 6 hrs, depending on weather conditions. (The drying time might be elongated according to temperature and humidity conditions)

ACCORDING TO 2004/42/EK

PHASE II,
Subcategory a,
Matt coatings for interior walls and ceilings, Value limit V.O.C.= 30gr/lit, max VOC.=10gr/lit (ready to use product)



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Recommended application systems

Interior walls

New surfaces

Preparation

For smoother results on new surfaces, it is recommended to use Berling's Stuco Grid putty, following the application instructions.

STUCO GRID
2 coats

Primer

Prime with Nature Aquafix or Acrylic Emulsion Primer, following the application instructions. When choosing dark shades, prime with Acrylic White Primer tinted in close or similar shade according to Berling's tinting system, to reduce the number of final coats.

**AQUAFIX NATURE
ACRYLIC EMULSION PRIMER**

ACRYLIC WHITE PRIMER

1 coat

Final coating

For a uniform and impressive result apply 2 coatings with Petite Satin.

PETITE SATIN
2 coats

• Old- already painted surfaces

Preparation

On already painted but healthy, non-stained surfaces, no special preparation is required. In the case of puttied surfaces, sanding with sandpaper is required.

Primer

For surfaces that are puttied and sanded and surfaces that have been chalked or covered with distemper paint or lime, it is required to be primed with Berling's primer Nature Aquafix.

**AQUAFIX NATURE
EXPERT PRIMER**

1 coat

If the surface is stained by exhaust gases, smoke or other household pollutants, it is required to be primed with Berling's EXPERT primer, before applying the product.

Final coating

For a uniform and impressive result apply 2 coatings with Petite Satin.

PETITE SATIN
2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Recommended application systems

Plasterboard surfaces

• New surfaces

Preparation

If necessary, putty with Berling Stuco Grid, following its application instructions.

STUCO GRID

2 coats

Primer

In case of putting the whole surface, prime with Nature Aquafix, Acrylic emulsion primer or Berling Nanoprimer.

If no puttying procedure is required, then use Berling Plasterboard primer, following its application instructions. Plasterboard Primer can be tinted in close or similar shade according to Berling's tinting system, to reduce the number of final coats.

AQUAFIX NATURE ACRYLIC EMULSION PRIMER BERLING NANOPRIMER PLASTERBOARD PRIMER

1 coat

Final coating

For a uniform and impressive result apply 2 coatings with Petite Satin.

PETITE SATIN

2 coats

• Old-already painted surfaces

Preparation

On already painted but healthy, non-stained surfaces, no special preparation is required. In the case of puttied surfaces, sanding with sandpaper is required.

Primer

For surfaces that are puttied and sanded and surfaces that have been chalked or covered with distemper paint or lime, it is required to be primed with Berling's primer Nature Aquafix.

If the surface is stained by exhaust gases, smoke or other household pollutants, it is required to be primed with Berling's Nature Aquasil primer, before applying the product

AQUAFIX NATURE AQUASIL

1 coat

Final coating

For a uniform and impressive result apply 2 coatings with Petite Satin.

PETITE SATIN

2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.