

PETITE ECO

Excellent quality, matt, ecological emulsion paint

03.2025 V.06

Excellent quality, ecological, matt emulsion paint for indoor use, suitable for walls and ceilings. Ideal for interior use and especially for children's bedrooms. It is easily applied and demonstrates excellent coverage and washable properties. It has very good adhesion on all properly prepared surfaces and high whiteness.



Stir well before use



Coverage:
17-20 m²/lt



Drying time:
Touch dry 1-2hrs



Thinning
with water at a percentage of 10-15% by volume



Paint:
Roller



Paint:
Brush



Paint:
Airless gun

Product Characteristics

- Full matt finish
- Excellent coverage and performance
- Very good adhesion
- Excellent washability
- High whiteness
- Easy to apply
- Almost odorless
- Very low Volatile Organic Compounds content.
- Awarded with the EU Ecolabel. (Registry No EL / 044/001).

Shades

Available in white and three bases (Base A, Base B and Base C) to create thousands of shades with Berling's tinting system

Packaging:

White

0.375lt

0.75lt

3lt

10lt

Bases

0.75lt

3lt

9lt



EPD[®]

THE INTERNATIONAL EPD[®] SYSTEM

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



V.O.C	10 gr/lit (Maximum Volatile Organic Compounds content ready for use).
Density	1,40± 0,03gr/cm ³ (ISO 2811) (for white).
Viscosity	90-105 K.U., 25°C (ASTM D562) (for white).
pH	7,7-8,7
Performance	17-20m ² /lit, per coating.
Wet Abrasion Resistance	Class 1 (EN ISO 11998, EN 13300)
Gloss	2-2,5 units at an angle 60°.
Thinning	Thin with water at a percentage of 10-15% by volume, depending on the application method.
Application	The product is applied by brush or roller or airless gun.
Drying	Touch dry 1-2hrs, depending on the weather conditions. (The drying time might be elongated according to temperature and humidity conditions)
Recoating	Repaint after 6 hrs, depending on weather conditions. (The drying time might be elongated according to temperature and humidity conditions)

ACCORDING TO 2004/42/EK

PHASE II,
Subcategory a,
Matt coatings for interior walls and ceilings, Value limit V.O.C.= 30gr/lit, max VOC.=10gr/lit (ready to use product)



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Recommended application systems

Interior walls

• New surfaces

Preparation

For smoother results on new surfaces, it is recommended to use Berling's Stuco Grid putty, following the application instructions.

STUCO GRID
2 coats

Primer

Prime with Nature Aquafix or Acrylic Emulsion Primer, following the application instructions. When choosing dark shades, prime with Acrylic White Primer tinted in close or similar shade according to Berling's tinting system, to reduce the number of final coats.

**AQUAFIX NATURE or
ACRYLIC EMULSION PRIMER
or ACRYLIC WHITE PRIMER**

1 coat

Final coating

For a uniform and impressive result apply 2 coatings with PETITE ECO.

PETITE ECO
2 coats

• Old- already painted surfaces

Preparation

On already painted but healthy, non-stained surfaces, no special preparation is required. In the case of puttied surfaces, sanding with sandpaper is required.

Primer

For surfaces that are puttied and sanded and surfaces that have been chalked or covered with distemper paint or lime, it is required to be primed with Berling's primer Nature Aquafix. For stained surface use EXPERT PRIMER

**AQUAFIX NATURE / EXPERT
PRIMER**

1 coat

Final coating

For a uniform and impressive result apply 2 coatings with PETITE ECO.

PETITE ECO
2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.