

HOBBY CRACKLE GLAZE

Crackle Decorative

05.2025 V.04

Acrylic, transparent coating, special to achieve crackled appearance on various surfaces. It can be applied on any suitably prepared surface.



Application Instructions

Prepare the surface to be painted and apply emulsion paint to the shade of your choice. This shade will be the substrate of the cracked surface you will create.

Then apply a coat of HOBBY Crackle Glaze with a brush to the surface by working the brush in one direction (do not cross the brush and do not pass the Crackle Glaze twice in the same spot) leaving enough of the material on the surface. Let the surface dry thoroughly.

When the product is complete dry (usually next day) apply emulsion paint tinted at the shade of your choice. A few minutes after the application the paint will begin to break by creating the crazing surface. Avoid choosing paints with high elasticity for achieving a better result.

The product is ready to use and need no thinning.

Ambient temperature should be at least 5°C and ambient humidity below 80%.

Packaging:

0,5lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



VOC	25gr/lit (Maximum Volatile Organic Compounds content ready for use).
Density	1,00 ± 0,03 gr /cm ³ (ISO 2811).
Viscosity	100-120 KU, 25°C (ASTM D562).
pH	7,5-8,5
Thinning	The product is ready to use and needs no thinning.

ACCORDING TO 2004/42/EK

PHASE II,
Subcategory I,
Decorative finishing
Effects, VOC Limit
Value = 200gr/lit,
Maximum VOC
Value= 25gr/lit
(ready to use
product).



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.