

HOBBY EFFECTS

Acrylic semitransparent coating, suitable for creating many decorative styles for interior use.

05.2025 V.04

Acrylic semitransparent coating, suitable for creating many decorative styles for interior use. It is applied to surfaces that have already been coated with satin or matt emulsion or acrylic paint, which has previously been tinted to the desired, using Berling's tinting system. With HOBBY Effects Berling gives the user the opportunity to use his imagination and create the style of his choice.



Stir well before use



Coverage:
18-20 m²/lt



Drying time:
4-6 hours



Thinning
Ready to use product.



Paint:
Roller



Paint:
Brush

Product Characteristics

- Decorative
- According to 2004/42/EC
- Can be tinted

Shades

It can be tinted by using Berling tinting system.

Packaging:

0,5lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



VOC	200gr/lit (Maximum Volatile Organic Compounds content ready for use).
Density	1,10 ± 0,03 gr /cm ³ (ISO 2811).
Coverage	18 - 20m ² /lit, depending on the type of style.
Thinning	Ready to use product. No thinning is required.
Application	The product is applied with a brush, sponge, or other decorative styling tool.
Drying time	4-6 hours. (These times may be prolonged depending on temperature and humidity).

ACCORDING TO 2004/42/EK

PHASE II,
Subcategory I,
Decorative finishing
Effects, VOC Limit
Value = 200gr/lit,
Maximum VOC
Value= 200gr/lit
(ready to use
product).



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Recommended application systems

Interior surfaces

APPLICATION INSTRUCTIONS

First, apply a plastic or acrylic paint to the surface in the color of your choice and allow it to dry thoroughly. Then, pour the HOBBY Effects into a paint tray.

To create the desired patterns, you can use a brush, sponge, or another decorative technique tool.

If using a brush, dip it into the HOBBY Effects and apply it by moving the brush in random directions across the surface.

If using a sponge, dip it into the HOBBY Effects and press it lightly onto the surface to achieve random imprints.

Special note:

After applying the material in three coats and ensuring the surface is properly covered, it requires 7 days to reach full durability. In case of writing with a marker, cleaning is quick using a slightly damp cloth or paper. If you find that a marker leaves shadows after cleaning, use a suitable solvent to remove it and try a different marker.

The material retains its durability even after repeated cleanings, provided that the appropriate cleaning solvents are used correctly. After many uses (cleanings), you may notice a loss of gloss on the material. This is normal and does not affect its performance. However, it is advisable to apply a new coat after extensive use so that the desired result lasts longer.