




**ACRYLIC ROAD MARKING PAINT YELLOW  
 116826**
**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** ACRYLIC ROAD MARKING PAINT YELLOW  
116826
- Other means of identification:**
- UFI:** SC90-E0GP-A001-X5HK
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
 Relevant uses (Professional users): Road sign paint: zebra crossings, yellow boxes, etc...  
 Relevant uses (Industrial user): Road sign paint: zebra crossings, yellow boxes, etc...  
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
 Berling S.A.  
 Thesi Aghia Paraskevi  
 32011 Inofita - Viotia - Greece  
 Phone: +302262031663 - Fax: +302262031293  
 info@berling.gr  
 www.berling.gr
- 1.4 Emergency telephone number:**

**SECTION 2: HAZARDS IDENTIFICATION \*\***

- 2.1 Classification of the substance or mixture:**
- CLP Regulation (EC) No 1272/2008:**  
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412  
 Eye Irrit. 2: Eye irritation, Category 2, H319  
 Flam. Liq. 2: Flammable liquids, Category 2, H225  
 Lact.: Reproductive toxicity, effects on or via lactation, H362  
 Repr. 2: Reproductive toxicity, Category 2, H361d  
 Skin Irrit. 2: Skin irritation, Category 2, H315  
 STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373
- 2.2 Label elements:**
- CLP Regulation (EC) No 1272/2008:**  
 Danger
- 


- Hazard statements:**  
 Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.  
 Eye Irrit. 2: H319 - Causes serious eye irritation.  
 Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
 Lact.: H362 - May cause harm to breast-fed children.  
 Repr. 2: H361d - Suspected of damaging the unborn child.  
 Skin Irrit. 2: H315 - Causes skin irritation.  
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

## ACRYLIC ROAD MARKING PAINT YELLOW 116826

### SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
 P302+P352: IF ON SKIN: Wash with plenty of water.  
 P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313: IF exposed or concerned: Get medical advice/attention.  
 P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.  
 P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

#### Substances that contribute to the classification

Xylene (CAS: 1330-20-7); Toluene (CAS: 108-88-3); Alkanes, C14-17, chloro (CAS: 85535-85-9)

**UFI:** SC90-E0GP-A001-X5HK

#### 2.3 Other hazards:

Product contains PBT/vPvB substances: Alkanes, C14-17, chloro  
 Endocrine-disrupting properties: The product does not meet the criteria.

\*\* Changes with regards to the previous version

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

#### 3.1 Substance:







Not relevant

#### 3.2 Mixture:

**Chemical description:** Mixture composed of additives, aggregates, pigments and resins in solvents

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(1)</sup></b> Self-classified	<b>10 - &lt;20%</b>
	Regulation 1272/2008 Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger 	
CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX	<b>Toluene<sup>(1)</sup></b> ATP CLP00	<b>10 - &lt;20%</b>
	Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger 	
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	<b>acetone<sup>(1)</sup></b> ATP CLP00	<b>1 - &lt;3%</b>
	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger 	
CAS: 85535-85-9 EC: 287-477-0 Index: 602-095-00-X REACH: 01-2119519269-33-XXXX	<b>Alkanes, C14-17, chloro<sup>(1)</sup></b> ATP ATP01	<b>1 - &lt;3%</b>
	Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Lact.: H362; EUH066 - Warning 	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	<b>N-butyl acetate<sup>(2)</sup></b> ATP CLP00	<b>&lt;1%</b>
	Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning 	
CAS: 872-50-4 EC: 212-828-1 Index: 606-021-00-7 REACH: 01-2119472430-46-XXXX	<b>N-methyl-2-pyrrolidone<sup>(2)</sup></b> ATP ATP09	<b>&lt;1%</b>
	Regulation 1272/2008 Eye Irrit. 2: H319; Repr. 1B: H360D; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger 	

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878




<sup>(2)</sup> Substance with a Union workplace exposure limit

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW  
116826**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\* (continued)**

Identification	Chemical name/Classification	Concentration
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(2)</sup></b> ATP CLP00	<1%
	Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning 	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	<b>2-methoxy-1-methylethyl acetate<sup>(2)</sup></b> ATP ATP01	<1%
	Regulation 1272/2008 Flam. Liq. 3: H226 - Warning 	
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	<b>Ethylbenzene<sup>(2)</sup></b> ATP ATP06	<1%
	Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger 	

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

(2) Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**Other information:**

Identification	Specific concentration limit
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	% (w/w) >=10: STOT SE 3 - H335

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Xylene CAS: 1330-20-7 EC: 215-535-7	Not relevant	1100 mg/kg	
	17 mg/L		
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Not relevant	Not relevant	
	Not relevant	17,2 mg/L	

\*\* Changes with regards to the previous version

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW**  
**116826****SECTION 4: FIRST AID MEASURES (continued)****4.3 Indication of any immediate medical attention and special treatment needed:**

Not relevant

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:****Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

**Unsuitable extinguishing media:**

Water jet

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EEC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

**6.4 Reference to other sections:**

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -

## ACRYLIC ROAD MARKING PAINT YELLOW 116826

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

##### A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

##### B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

##### C.- Technical recommendations on general occupational hygiene

**PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT.** Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

##### D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

#### 7.2 Conditions for safe storage, including any incompatibilities:

##### A.- Specific storage requirements

Minimum Temp.: 5 °C  
Maximum Temp.: 35 °C  
Maximum time: 0 Months

##### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Xylene <sup>(1)</sup> CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
Ethylbenzene <sup>(1)</sup> CAS: 100-41-4 EC: 202-849-4	IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>
	IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>
	IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate <sup>(1)</sup> CAS: 108-65-6 EC: 203-603-9	IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>
	IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>
acetone CAS: 67-64-1 EC: 200-662-2	IOELV (8h)	500 ppm	1210 mg/m <sup>3</sup>
	IOELV (STEL)		
Xylene <sup>(1)</sup> CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
N-methyl-2-pyrrolidone <sup>(1)</sup> CAS: 872-50-4 EC: 212-828-1	IOELV (8h)	10 ppm	40 mg/m <sup>3</sup>
	IOELV (STEL)	20 ppm	80 mg/m <sup>3</sup>

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW  
116826**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Toluene <sup>(1)</sup>	IOELV (8h)	50 ppm	192 mg/m <sup>3</sup>
CAS: 108-88-3    EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m <sup>3</sup>

<sup>(1)</sup> Skin

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	384 mg/kg	Not relevant
	Inhalation	384 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	186 mg/kg	Not relevant
	Inhalation	Not relevant	2420 mg/m <sup>3</sup>	1210 mg/m <sup>3</sup>	Not relevant
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	47,9 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	6,7 mg/m <sup>3</sup>	Not relevant
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	11 mg/kg	Not relevant	11 mg/kg	Not relevant
	Inhalation	600 mg/m <sup>3</sup>	600 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	4,8 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	14,4 mg/m <sup>3</sup>	40 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	796 mg/kg	Not relevant
	Inhalation	Not relevant	550 mg/m <sup>3</sup>	275 mg/m <sup>3</sup>	Not relevant
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	180 mg/kg	Not relevant
	Inhalation	Not relevant	293 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Not relevant

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Not relevant	Not relevant	8,13 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	226 mg/kg	Not relevant
	Inhalation	226 mg/m <sup>3</sup>	226 mg/m <sup>3</sup>	56,5 mg/m <sup>3</sup>	56,5 mg/m <sup>3</sup>
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Not relevant	Not relevant	62 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	62 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	200 mg/m <sup>3</sup>	Not relevant
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Not relevant	Not relevant	0,58 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	28,75 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	2 mg/m <sup>3</sup>	Not relevant

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW**  
**116826**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Not relevant	2 mg/kg	Not relevant
	Dermal	6 mg/kg	Not relevant	6 mg/kg	Not relevant
	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	Oral	Not relevant	Not relevant	0,85 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	2,4 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	3,6 mg/m <sup>3</sup>	4,5 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Not relevant	Not relevant	36 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	320 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	33 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	Not relevant	1,6 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	15 mg/m <sup>3</sup>	Not relevant

**PNEC:**

Identification				
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Not relevant	Sediment (Marine water)	12,46 mg/kg
Toluene CAS: 108-88-3 EC: 203-625-9	STP	13,61 mg/L	Fresh water	0,68 mg/L
	Soil	2,89 mg/kg	Marine water	0,68 mg/L
	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Not relevant	Sediment (Marine water)	16,39 mg/kg
acetone CAS: 67-64-1 EC: 200-662-2	STP	100 mg/L	Fresh water	10,6 mg/L
	Soil	29,5 mg/kg	Marine water	1,06 mg/L
	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Not relevant	Sediment (Marine water)	3,04 mg/kg
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	STP	80 mg/L	Fresh water	0,001 mg/L
	Soil	11,9 mg/kg	Marine water	0,0002 mg/L
	Intermittent	Not relevant	Sediment (Fresh water)	13 mg/kg
	Oral	0,01 g/kg	Sediment (Marine water)	2,6 mg/kg
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,09 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,098 mg/kg
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	STP	10 mg/L	Fresh water	0,25 mg/L
	Soil	0,07 mg/kg	Marine water	0,025 mg/L
	Intermittent	5 mg/L	Sediment (Fresh water)	1,09 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,109 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Not relevant	Sediment (Marine water)	12,46 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,064 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,329 mg/kg

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW  
116826**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**



Identification				
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg

**8.2 Exposure controls:**



**A.- Individual protection measures, such as personal protective equipment**

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.  
All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN ISO 16321-1:2022 + EN ISO 16321-3:2022 EN ISO 18526-(1,2,3,4):2020 EN ISO 18526-(1,2,3,4):2020 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013/A1:2021 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2019 EN ISO 20345:2022 EN 13832-1:2018	Replace boots at any sign of deterioration.



**F.- Additional emergency measures**

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

- CONTINUED ON NEXT PAGE -

## ACRYLIC ROAD MARKING PAINT YELLOW 116826

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	27,62 % weight
V.O.C. density at 25 °C:	411,54 kg/m <sup>3</sup> (411,54 g/L)
Average carbon number:	7,05
Average molecular weight:	96,44 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 25 °C:	500 kg/m <sup>3</sup> (500 g/L)
EU limit for the product (Cat. A.I):	500 g/L (2010)
Components:	SOLVENT E - 20 % v/v

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Not relevant *
Colour:	According to the markings on the package
Odour:	Aromatic
Odour threshold:	Not relevant *

**Volatility:**

Boiling point at atmospheric pressure:	112 °C
Vapour pressure at 25 °C:	6617 Pa
Vapour pressure at 50 °C:	19006,7 Pa (19,01 kPa)
Evaporation rate at 25 °C:	Not relevant *

**Product description:**

Density at 25 °C:	1460,2 - 1520,2 kg/m <sup>3</sup>
Relative density at 25 °C:	1,46 - 1,52
Dynamic viscosity at 25 °C:	1693,7 - 1618,22 mPa·s
Kinematic viscosity at 25 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 25 °C:	Not relevant *
Partition coefficient n-octanol/water 25 °C:	Not relevant *
Solubility in water at 25 °C:	Not relevant *
Solubility properties:	Not relevant *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW**  
**116826**
**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Decomposition temperature: Not relevant \*

Melting point/freezing point: Not relevant \*

**Flammability:**

Flash Point: 7 °C

Flammability (solid, gas): Not relevant \*

Autoignition temperature: 315 °C

Lower flammability limit: Not relevant \*

Upper flammability limit: Not relevant \*

**Particle characteristics:**

Median equivalent diameter: Not relevant \*

**9.2 Other information:**
**Information with regard to physical hazard classes:**

Explosive properties: Not relevant \*

Oxidising properties: Not relevant \*

Corrosive to metals: Not relevant \*

Heat of combustion: Not relevant \*

Aerosols-total percentage (by mass) of flammable components: Not relevant \*

**Other safety characteristics:**

Surface tension at 25 °C: Not relevant \*

Refraction index: Not relevant \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**
**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

In case of prolonged thermal treatment at temperatures greater than 200 °C, the decomposition products are aromatic amines (3,3'-dichlorobenzidine)

**SECTION 11: TOXICOLOGICAL INFORMATION \*\***
**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW  
116826**

**SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)**

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

**A- Ingestion (acute effect):**

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

**B- Inhalation (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

**C- Contact with the skin and the eyes (acute effect):**

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Causes serious eye irritation.

**D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Xylene (3: Not classifiable as to its carcinogenicity to humans); Ethylbenzene (2B: Possibly carcinogenic to humans); C.I.Pigment yellow 83 (1: Carcinogenic to humans); Xylene (3: Not classifiable as to its carcinogenicity to humans); Alkanes, C14-17, chloro (2B: Possibly carcinogenic to humans); Toluene (3: Not classifiable as to its carcinogenicity to humans)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging the unborn child.

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**F- Specific target organ toxicity (STOT) - single exposure:**

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation vapour	76 mg/L (4 h)	Rat

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW  
116826**
**SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)**

Identification	Acute toxicity		Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	3523 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Toluene CAS: 108-88-3 EC: 203-625-9	LD50 oral	5580 mg/kg	Rat
	LD50 dermal	12124 mg/kg	Rat
	LC50 inhalation vapour	28,1 mg/L (4 h)	Rat
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation vapour	23,4 mg/L (4 h)	Rat
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rat
	LC50 inhalation vapour	>20 mg/L	
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	3523 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	17 mg/L	Rat
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation vapour	30 mg/L (4 h)	Rat
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation vapour	17,2 mg/L	Rat

**11.2 Information on other hazards:**
**Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

**Other information**

Not relevant

\*\* Changes with regards to the previous version

**SECTION 12: ECOLOGICAL INFORMATION \*\***

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

**12.1 Toxicity:**
**Acute toxicity:**

Identification	Concentration		Species	Genus
	LC50	EC50		
Toluene CAS: 108-88-3 EC: 203-625-9	LC50	5,5 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50	3,78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	Not relevant		
acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	Not relevant		
	EC50	Not relevant		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW  
116826**

**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Concentration		Species	Genus
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	LC50	832 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	4897 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	500 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Not relevant		
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
acetone CAS: 67-64-1 EC: 200-662-2	NOEC	Not relevant		
	NOEC	2212 mg/L	Daphnia magna	Crustacean
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC	Not relevant		
	NOEC	23,2 mg/L	Daphnia magna	Crustacean
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	NOEC	Not relevant		
	NOEC	12,5 mg/L	Daphnia magna	Crustacean
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	NOEC	Not relevant		
	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Not relevant	Concentration	16 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	94 %
Toluene CAS: 108-88-3 EC: 203-625-9	BOD5	2,5 g O2/g	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	100 %
acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	96 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	5 days
	BOD5/COD	Not relevant	% Biodegradable	84 %
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	BOD5	1,09 g O2/g	Concentration	100 mg/L
	COD	1,6 g O2/g	Period	28 days
	BOD5/COD	0,68	% Biodegradable	73 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	88 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Not relevant	Concentration	785 mg/L
	COD	Not relevant	Period	8 days
	BOD5/COD	Not relevant	% Biodegradable	100 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	90 %

**12.3 Bioaccumulative potential:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW  
116826**
**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**
**Substance-specific information:**

Identification	Bioaccumulation potential	
	BCF	Pow Log
Xylene CAS: 1330-20-7 EC: 215-535-7	26	3.16
	Potential	Low
	90	2.73
Toluene CAS: 108-88-3 EC: 203-625-9	90	2.73
	Potential	Moderate
	1	-0.24
acetone CAS: 67-64-1 EC: 200-662-2	1	-0.24
	Potential	Low
	4	1.78
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	4	1.78
	Potential	Low
	0.23	-0.46
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	0.23	-0.46
	Potential	Low
	9	2.77
Xylene CAS: 1330-20-7 EC: 215-535-7	9	2.77
	Potential	Low
	1	0.43
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	1	0.43
	Potential	Low
	1	3.15
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	1	3.15
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
	Koc	Conclusion	Henry	623 Pa·m <sup>3</sup> /mol
Xylene CAS: 1330-20-7 EC: 215-535-7	537	Moderate	Dry soil	Yes
	Surface tension	Not relevant	Moist soil	Yes
	178	Moderate	Dry soil	Yes
Toluene CAS: 108-88-3 EC: 203-625-9	2,793E-2 N/m (25 °C)	Moderate	Dry soil	Yes
	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes
	1	Very High	Dry soil	Yes
acetone CAS: 67-64-1 EC: 200-662-2	2,304E-2 N/m (25 °C)	Very High	Dry soil	Yes
	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
	Not relevant	Not relevant	Dry soil	Not relevant
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Not relevant	Not relevant	Dry soil	Not relevant
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Not relevant
	Not relevant	Not relevant	Dry soil	Not relevant
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	4,007E-2 N/m (25 °C)	Not relevant	Dry soil	Not relevant
	Surface tension	4,007E-2 N/m (25 °C)	Moist soil	Not relevant
	202	Moderate	Dry soil	Yes
Xylene CAS: 1330-20-7 EC: 215-535-7	520	Moderate	Dry soil	Yes
	Surface tension	Not relevant	Moist soil	Yes
	2,859E-2 N/m (25 °C)	Moderate	Dry soil	Yes
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	798,44 Pa·m <sup>3</sup> /mol	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Product contains PBT/vPvB substances: Alkanes, C14-17, chloro

**12.6 Endocrine disrupting properties:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

## ACRYLIC ROAD MARKING PAINT YELLOW 116826

### SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

Endocrine-disrupting properties: The product does not meet the criteria.

**12.7 Other adverse effects:**

Not described

*\*\* Changes with regards to the previous version*

### SECTION 13: DISPOSAL CONSIDERATIONS

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### SECTION 14: TRANSPORT INFORMATION

**Transport of dangerous goods by land:**

With regard to ADR 2025 and RID 2025:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
- Labels: 3
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: 163, 367, 640D, 650
- Tunnel restriction code: D/E
- Physico-Chemical properties: see section 9
- Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by sea:**

With regard to IMDG 42-24:

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW  
116826**

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** II
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**  
Special regulations: 367, 163  
EmS Codes: F-E, S-E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2026:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): *Alkanes, C14-17, chloro (85535-85-9)* ; *N-methyl-2-pyrrolidone (872-50-4)*
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000,000	50000,000

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains N-methyl-2-pyrrolidone. 1. | Shall not be placed on the market as a substance on its own or in mixtures in a

- CONTINUED ON NEXT PAGE -

**ACRYLIC ROAD MARKING PAINT YELLOW**  
**116826****SECTION 15: REGULATORY INFORMATION (continued)**

concentration equal to or greater than 0,3 % after 9 May 2020 unless manufacturers, importers and downstream users have included in the relevant chemical safety reports and safety data sheets, Derived No-Effect Levels (DNELs) relating to exposure of workers of 14,4 mg/m<sup>3</sup> for exposure by inhalation and 4,8 mg/kg/day for dermal exposure. | 2. | Shall not be manufactured, or used, as a substance on its own or in mixtures in a concentration equal to or greater than 0,3 % after 9 May 2020 unless manufacturers and downstream users take the appropriate risk management measures and provide the appropriate operational conditions to ensure that exposure of workers is below the DNELs specified in paragraph 1. | 3. | By way of derogation from paragraphs 1 and 2, the obligations laid down therein shall apply from 9 May 2024 in relation to placing on the market for use, or use, as a solvent or reactant in the process of coating wires.

Laboral exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2022/431, of the European Parliament and of the Council, of March 9, 2022, amending Directive 2004/37/EC, relating to the protection of workers against risks related to exposure to carcinogens or mutagens during work.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION \*\*****Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances

Xylene (1330-20-7)

Substances that contribute to the classification (SECTION 2):

- New declared substances

Xylene (1330-20-7)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Hazard statements
- Precautionary statements

**Texts of the legislative phrases mentioned in section 2:**

H373: May cause damage to organs through prolonged or repeated exposure.

H315: Causes skin irritation.

H362: May cause harm to breast-fed children.

H412: Harmful to aquatic life with long lasting effects.

H361d: Suspected of damaging the unborn child.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

**ACRYLIC ROAD MARKING PAINT YELLOW**  
**116826****SECTION 16: OTHER INFORMATION \*\* (continued)**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.  
Acute Tox. 4: H332 - Harmful if inhaled.  
Aquatic Acute 1: H400 - Very toxic to aquatic life.  
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Lact.: H362 - May cause harm to breast-fed children.  
Repr. 1B: H360D - May damage the unborn child.  
Repr. 2: H361d - Suspected of damaging the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.  
STOT SE 3: H335 - May cause respiratory irritation.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

**Classification procedure:**

STOT RE 2: Calculation method  
Skin Irrit. 2: Calculation method  
Lact.: Calculation method  
Aquatic Chronic 3: Calculation method  
Repr. 2: Calculation method  
Flam. Liq. 2: Calculation method (2.6.4.3)  
Eye Irrit. 2: Calculation method

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
LogPOW: Octanolwater partition coefficient  
Koc: Partition coefficient of organic carbon  
UFI: unique formula identifier  
IARC: International Agency for Research on Cancer

*\*\* Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -