

SUPER YACHT VARNISH

Elastic and energy upgrade hybrid coating for roofs

04.2024 V.03

High quality, transparent, alkyd wood varnish for interior and exterior wood. Used for the protection of woods such as garden furniture, doors, wooden shutters as well as wooden yacht surfaces. It has great resistance to weather changes and protects from solar radiation. It is easily applied forming a transparent elastic membrane.



Stir well before use



Coverage:
10-12 m²/lt



Drying time:
Touch dry after 4 to 6 hours.



Thinning
with White Spirit
at a percentage
up to 12% by
volume



Paint:
Roller



Paint:
Brush

Product Characteristics

- Very good adhesion.
- High coverage.
- Resistance to weather changes
- Protection from solar radiation
- Easy to apply.
- Great elasticity.
- Suitable for exterior and interior use
- Transparent
- Gloss, satin or matt finish

Shades

Available in colorless and in gloss, satin and matt finish.

Packaging:

0.75lt
2.5lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



V.O.C	400gr/lit (maximum VOC content of thinned-ready to use products).
Density	0,91 - 0,96gr/cm ³ (ISO 2811),
Viscosity	70 - 110 K.U., 25°C (ASTM D562),
Coverage	10 - 12m ² /lit, depending of the absorbency and the kind of the surface
Gloss (under 60°)	Gloss> 90 units Satin: 45-65 Matt: 10-25
Thinning	Thinned with White Spirit at a percentage up to 12% by volume
Application	Applied by brush or roller
Drying time	Touch dry after 4 to 6 hours (These times may be elongated depending on temperature and humidity)
Reapplication	After 24 hours. (These times may be elongated depending on temperature and humidity)

ACCORDING TO 2004/42/EK

PHASE II,
Subcategory-e,
interior exterior trim
varnishes, VOC
Content limit
value.= 400gr/lit,
Max. VOC content.
= 400gr/lit (thinned-
ready to use
products).



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with white spirit. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

Recommended application systems

Old and new surfaces

- **New Surfaces/ Already painted surfaces**

Preparation

Dust, pieces of wood, etc. are removed on new surfaces by rubbing with sandpaper. For already varnished surfaces, first rub with sandpaper and then clean with a cloth dipped in White Spirit. For varnished wood in poor condition, completely remove the old coating, using Berling's Paint Remover and then follow the same painting procedure, as in case of new wood.

Primer

For the protection of wood from fungus and insects apply wood stain Fungistop, following its protection instructions.

FUNGISTOP
1 coat

Final coating

For a uniform and impressive result apply 2 coatings of Super Yacht Varnish

SUPER YACHT VARNISH
2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.