

TEAK AND DECKING OIL

Oil for the protection of wooden surfaces

05.2025 V.04

Mixture of oils, waxes and special additives with high penetration for protection and treatment of wooden surfaces. It is easily absorbed, revitalizes and protects wood. It is suitable for indoor and outdoor use, ideal for treating garden furniture from hardwoods such as teak, mahogany, oak, beech, rosewood as well as decks and decorative wood in boats.



Stir well before use



Coverage:
10-15 m²/lt



Drying time:
Between 3 to 4 hrs.



Thinning
Ready to use.



Paint:
Roller



Paint:
Brush

Product Characteristics

- High protection of wood against moisture, UV radiation, salinity.
- High penetration.
- It replaces natural oils and resins that the wood lose over time.
- Easy application.
- Great performance.
- High resistance to changes in weather conditions.
- Harmonized with Directive 2004/42/EC.

Packaging:
0,75lt
4lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



V.O.C	400gr/lit (Maximum Volatile Organic Compounds content ready for use).
Viscosity	12-18 K.U., 25°C (ASTM D562).
Performance	10-15 m ² /lit,
Thinning	The product is ready for use and does not require thinning.
Application	The product is applied by brush or roller
Drying	Touch dry 3-4 hrs, depending on the weather conditions. (The drying time might be elongated according to temperature and humidity conditions)
Recoating	Repaint after 48 hrs, depending on weather conditions. (The drying time might be elongated according to temperature and humidity conditions)

ACCORDING TO 2004/42/EK

Subcategory i, one-pack performance coatings/floor varnish, Max VOC Content limit value:400gr/lit Max VOC content:400gr/lit (ready to use product).



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with white spirit. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Recommended application systems

Interior/ Exterior walls

- New surfaces / Already painted surfaces

Preparation

The surface to be painted must be completely dry and clean. The product is applied by brush or cloth. In order to achieve good penetration into the wood, the product is coated in the direction of the wood lines.

Application Instructions

The new surfaces are lightly rubbed with sandpaper and any dust and pieces of wood are removed before the application. The product is then applied with a brush or cloth in one or two coatings. After 5 minutes of the application, wipe well with a cloth.

On already painted with Teak & Decking Oil surfaces, the product is applied with a brush or cloth in one or two coatings. After applying, let it for 5 minutes and then wipe well with a cloth. After use, clean with White Spirit the paint tools. The washes are treated as hazardous according to applicable legislation and local regulations.

TEAK AND DECKING OIL

2 COATS