

# ACRYLIC ROAD MARKING PAINT

High-quality, specialized, fast-drying acrylic paint for road markings.



03.2026 V.04

High-quality, specialized, fast-drying acrylic paint for road markings, as well as for concrete and industrial floors, offering excellent resistance to weather changes and mechanical stress. For increased reflectivity, special reflective glass beads can be used



**Mix well before use**



**Coverage:**  
9-10m<sup>2</sup>/lt



**Drying time:**  
Surface dry in 10-20 min



**Thinning:**  
with Berling's Solvent E at 10% by volume



**Paint:**  
Roller



**Paint:**  
Airless gun

## Product Characteristics

- Very good adhesion
- High performance and coverage
- High resistance to wear and tear.
- Complies with the requirements of the International Standard EN 1871 : 2000.

## Shades

Available in white and yellow.

## Packaging:

**White Acrylic:**  
3.1lt  
15,6 lt.

**Yellow acrylic:**  
0.6lt  
3.1lt  
15,6 lt.



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

## Τεχνικά Χαρακτηριστικά



<b>V.O.C.</b>	500gr/lit (Maximum Volatile Organic Compounds content ready for use).
<b>Density</b>	1,53±0,03gr/cm <sup>3</sup> (ISO 2811), depending on shade
<b>Viscosity</b>	95-110 K.U., 25°C (ASTM D562), depending on shade
<b>Coverage</b>	9 - 10m <sup>2</sup> /lit, at dry film thickness 50µm.
<b>Thinning</b>	Thinned with Solvent E up to 10% by volume, depending on the application method
<b>Application</b>	The product is applied by roller or airless gun
<b>Drying time</b>	Surface dry in 10 to 20 minutes (these times may be extended depending on temperature and humidity)
<b>Recoating</b>	After 20 minutes, depending on weather conditions.

### ACCORDING TO 2004/42/EK

PHASE II,  
Subcategory i: one-  
pack performance  
coatings. Content  
limit value: V.O.C  
500gr/Lt.

Maximum value  
V.O.C: 500gr/Lt.  
Thinning up to 10%  
by volume with  
solvent E.



### Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



### Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with Solvent E. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.  
**For further information ask for the Safety Data Sheet of the product.**

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

## Recommended application systems



### INTERIOR/EXTERIOR USE

- New / Old surfaces

### APPLICATION INSTRUCTIONS

Dilute with Solvent E up to 10% by volume and then stir the product well before use.

- Surfaces to be painted must be dry and clean. Apply the product using a road marking machine, or with a brush or roller after appropriate thinning.
- Application should be carried out at ambient temperatures between 10°C and 35°C and maximum relative humidity of 80%. To achieve higher reflectivity, after applying the product and before it dries, spread the glass beads onto the wet paint surface. The ratio is 2 parts paint to 1 part glass beads.
- After use, clean painting tools with Berling Solvent E. Wash residues must be handled as hazardous waste in accordance with current legislation and local regulations.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.