

BETOFLOOR

Floor Paint



06.2025 V.04

Excellent quality, solvent based paint, suitable for painting cement floors, pavements, plaster, bricks, and stones. It is suitable for interior and exterior use, with very good adhesion, blocks alkali salts coming from the surfaces. It has good resistance to mechanical stress and to weather changes.



Stir well before use



Coverage:
9-11 m²/lt



Drying time:
Touch dry 2-4 hrs



Thinning
with White Spirit
at a percentage
up to 15% by
volume.



Paint:
Roller



Paint:
Brush

Product Characteristics

- Very good adhesion.
- High opacity and coverage.
- Resistance to mechanical stress.
- Great resistance against weather condition's changes and moisture.
- Harmonized with directive 2004/42/EC.

Packaging:

0,75lt
2.5lt
10lt



Shades

Available in WHITE, 1882 DARK GREY, 1881 LIGHT GREY, 1183 TILE - RED, 1184 GREEN.

WHITE

1881

1882

1183

1184

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



V.O.C	500gr/lit (Maximum Volatile Organic Compounds content ready for use).
Density	1,40-1,50 gr /cm ³ (ISO 2811)
Viscosity	100-110 K.U., 25°C (ASTM D562).
Performance	9-11 m ² /lit, per coat
Thinning	Thin with White Spirit at a percentage up to 15% by volume.
Application	The product is applied by brush or roller
Drying	Touch dry 2-4 hrs, depending on the weather conditions. (The drying time might be elongated according to temperature and humidity conditions)
Recoating	Repaint after 16 hrs, depending on weather conditions. (The drying time might be elongated according to temperature and humidity conditions)

ACCORDING TO 2004/42/EK

PHASE II,
Subcategory i, One
pack performing
coatings, max VOC
content limit value
= 500gr/lit, max
VOC content value
= 500gr/lit (ready to
use product).



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with white spirit. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Recommended application systems



Interior/ Exterior surface

Application Instructions

New Surfaces

Clean the surface and apply two coats of the product, after suitable thinning, with a time difference of 16 hours between them.

Old Surfaces

Clean properly already painted surfaces and remove any peeled or old paint left, using sandpaper. In case of chalked surfaces apply one coat of solvent based primer Fixateur, and then two coats of Betofloor, following the drying and repainting times. If the surface is clean, you may apply directly Betofloor, after appropriate sanding and suitable thinning.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.