

# STONE VARNISH

Stone Varnish



11.2022 V.03

Special acrylic impregnating varnish which penetrates even the smallest pore of stone, offering a uniform surface. Suitable for indoor and outdoor use for Karistos, Pilion states, etc.



**Stir well before use**



**Coverage:**  
5-9 m<sup>2</sup>/lt



**Drying time:**  
Between 1 to 2 hrs



**Thinning**  
No thinning is needed.



**Paint:**  
Roller



**Paint:**  
Brush

## Product Characteristics

- High penetrability.
- High resistance to weather condition changes
- Easy application

## Shades

Available in colorless.

## Packaging:

0.75lt  
4lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry  
Inofita Viotias, P.C. 32011, Greece  
tel.: +30 22620 31663, fax.: +30 22620 31293  
www.berling.gr /en info@berling.gr

## Technical Specifications



<b>V.O.C</b>	Up to 720gr/lit (Maximum Volatile Organic Compounds content ready for use).
<b>Density</b>	0,86 ± 0,03gr/cm <sup>3</sup> (ISO 2811).
<b>Viscosity</b>	15-30 sec, 25°C (Flow cup, 4 DIN 53211).
<b>Performance</b>	5-9m <sup>2</sup> /lit, depending on absorbency and surface type.
<b>Thinning</b>	The product is ready for use and does not require thinning.
<b>Application</b>	The product is applied by brush or roller.
<b>Drying time</b>	Touch dry after 1 to 2 hours. (These times can be prolonged depending on temperature and humidity).
<b>Recoat</b>	After 16 hours. (These times may be prolonged depending on temperature and humidity).

### ACCORDING TO 2004/42/EK

PHASE II,  
Subcategory h,  
Binding Primers,  
Max VOC content  
limit value = 750gr/lit,  
max VOC content  
value = 720gr/lit  
(ready to use  
product).



### Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



### Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.  
**For further information ask for the Safety Data Sheet of the product.**

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry  
Inofita Viotias, P.C. 32011, Greece  
tel.: +30 22620 31663, fax.: +30 22620 31293  
www.berling.gr /en info@berling.gr

## Recommended application systems



### New and old-already painted surfaces.

- **New surfaces**

#### Preparation

At new surfaces clean well removing dust

#### Primer

Not required.

#### Final coating

For a uniform and impressive result apply 2 coatings with STONE VARNISH.

**STONE VARNISH**  
2 coats

- **Old- already painted surfaces**

#### Preparation

In case of already painted with stone varnish surfaces, rub first with sandpaper and then clean thoroughly.

#### Primer

Not required.

#### Final coating

For a uniform and impressive result apply 2 coatings with STONE VARNISH.

**STONE VARNISH**  
2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry  
Inofita Viotias, P.C. 32011, Greece  
tel.: +30 22620 31663, fax.: +30 22620 31293  
[www.berling.gr](http://www.berling.gr) / [en info@berling.gr](mailto:info@berling.gr)