

# ACETONE

Solvent for Alkyd- Based Coatings



05.2024 V.01

ACETONE is a special solvent for diluting alkyd-based paints. Ideal for cleaning tools. Its special composition helps the alkyd coating to dry fast and evenly and give an excellent finish.



## • TECHNICAL DATA

**Basis:** Ketone

**Appearance:** liquid

**Colors:** Transparent

**Viscosity:** 0.33 mPa.s at 20°C

**Density:** 0.78±0,02 gr/cm<sup>3</sup>

**pH:** Not applicable

**Flash point:** 18°C

**Boiling point:** 56°C

**Vapour pressure:** 24.7 kPa

**Lower flammability:** 2.1% ( v/v)

**Upper flammability:** 13% ( v/v)



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

# ACETONE

Solvent for Alkyd- Based Coatings



**Stir well before use**



**Consumption:**  
Depending on the desired dilution.



**Paint:**  
Roller



**Paint:**  
Brush



**Paint:**  
Airless gun

## PREPARATION - APPLICATION

- You can clean a metal surface from oils and impurities using ACETONE.
- Add ACETONE after mixing the alkyd coating evenly.
- Add the appropriate amount according to the desired workability and instructions of the particular product.
- Stir until all the quantity in the container is completely homogenized.

## Packaging:

0.75lt



## Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



## Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.  
**For further information ask for the Safety Data Sheet of the product.**

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry  
Inofita Viotias, P.C. 32011, Greece  
tel.: +30 22620 31663, fax.: +30 22620 31293  
www.berling.gr /en info@berling.gr