

RADIATEUR

Enamel for heated surfaces.



11.2022 V.03

High quality gloss enamel, suitable for heated metallic surfaces, especially for central heating devices (radiators). It has high adhesion and opacity, resistance against high temperatures and great elasticity.



Stir well before use



Coverage:
10-12 m²/lt



Drying time:
Touch dry 2-4 hours



Thinning
with White Spirit
at a percentage
up to 15% by
volume.



Paint:
Roller



Paint:
Brush

Product Characteristics

- Very good adhesion.
- High performance and coverage.
- Great resistance against high temperatures.
- Great elasticity.
- Free of ammonia, lead, mercury and other heavy metals.
- Harmonized with directive 2004/42/EC.

Packaging:

0.75lt
2,5lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry
Inofita Viotias, P.C. 32011, Greece
tel.: +30 22620 31663, fax.: +30 22620 31293
www.berling.gr /en info@berling.gr

Technical Specifications



VOC	500gr/lit (max content in Volatile Organic Compounds of ready to use product).
Specific Gravity	1,18 ± 0,02gr/cm ³ (ISO 2811)
Viscosity	90 - 100 κ.u., 25°C (ASTM D562).
Gloss	> 85 units in 60° angle.
Coverage	11 - 14m ² /lit.
Thinning	Thin with White Spirit at a percentage up to 15% by volume.
Application	By brush or roller
Drying time	Touch dry 2-4 hours (Drying time might be elongated according to temperature and humidity conditions)
Recoating	After at least 12hours (Reapplication time depends on temperature and humidity)

ACCORDING TO 2004/42/EK

PHASE II ,
Subcategory i, One
pack performance
coatings, value limit
VOC = 500gr/lit,

max VOC value limit
= 500gr/lit (ready to
use product).



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry
Inofita Viotias, P.C. 32011, Greece
tel.: +30 22620 31663, fax.: +30 22620 31293
www.berling.gr /en info@berling.gr

Recommended application systems



Interior/ Exterior surfaces.

- New/ Old surfaces

Preparation

Surfaces to be painted must be dry and clean without rust, grease, etc. The product is applied by brush or roller after being suitably thinned on a well-prepared surface. Apply at temperatures between 10° C and 35° C and up to 80% in humidity. It is applied directly over new or old surfaces without requiring any primer.

After use, clean tools with White Spirit. Manage eluants as hazardous waste in accordance with the valid legislation and the local regulation.

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

BERLING SA- Paint Industry
Inofita Viotias, P.C. 32011, Greece
tel.: +30 22620 31663, fax.: +30 22620 31293
www.berling.gr / en_info@berling.gr